



CHRISTIE CP2000-ZX

Compact and Cost-effective Digital Cinema

Uses

Cinema/exhibition
Post-production
Digital mastering
Multi-media theatrical productions
Digital intermediate

The latest addition to Christie's world-renowned CP Series; the Christie CP2000-ZX is an all-in-one Digital Cinema projection solution. Designed for mid-sized screens – it's the brightest, highest performance projector with the lowest operating costs in its class.

Featuring a universal switching power supply for the lowest ripple, maximum performance and reliability, the Christie CP2000-ZX is up to 50% smaller by volume, yet brighter than the competition.

The ergonomic design offers simplicity of use in a robust and reliable package. The lens mount design is stable and solid. With improved airflow and better cooling, the CP2000-ZX promotes longer lamp life.

Expanding the Christie Digital Cinema projection family, the CP2000-ZX is built on 2K, 3-chip DLP Cinema® technology, featuring a contrast ratio greater than 2000:1 and reproduces 35.2 trillion colors.

Christie's Digital Cinema solutions speak directly to exhibitors' requirements – high performance and cost-effective. Easy to use, easy to install and easy to own.

Christie CP2000-ZX

Specifications

Built on 2K, 3-chip DLP Cinema® technology



The Christie CP2000-ZX is the most cost-effective solution for exhibitors with medium-sized screens.

With built in web services you can use a web browser from any computer in the building to control the projector.



The Control Display Panel (CDP™) provides local control of the projector for set up and daily operation.

Corporate Offices

USA – CYPRESS
PH: 714-236-8610
FX: 714-503-3385
sales-us@christiedigital.com

CANADA – KITCHENER
PH: 519-744-8005
FX: 519-749-3136
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
sales-france@christiedigital.com

HUNGARY / EASTERN EUROPE
PH: +36 (0)1 47 48 100
FX: +36 (0)1 47 48 452
sales-eeurope@christiedigital.com

SOUTH AFRICA
PH: +27 (0) 317 671 347
FX: +27 (0) 317 671 347
sales-africa@christiedigital.com

SINGAPORE
PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI
PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING
PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

KOREA
PH: +82 2 702 1601
FX: +82 2 702 1602
sales-korea@christiedigital.com

JAPAN
PH: +81 3 3599 7481
FX: +81 3 3599 7482
sales-japan@christiedigital.com

CONTRAST RATIO

- >2000:1 full field on/off

BRIGHTNESS UNIFORMITY

- >80% when displaying full white screen

TI DLP CINEMA™ TECHNOLOGY

- CineBlack™ Contrast Management
- CineCanvas™ Image Management
- CineLink™ Security Management
- CinePalette™ Color Management

DIGITAL MICROMIRROR DEVICE™

- 2K 3-chip DMD DLP Cinema®
- 2048 x 1080 pixels

INPUT LINE VOLTAGE

- Single phase 200–230 VAC (nominal)

COLOR PROCESSING (BIT DEPTH)

- 45-bit (3 x 15-bit resolution)

NUMBER OF COLORS

- 35.2 trillion

DIGITAL VIDEO INPUT

- Two SMPTE 292M; dual or single

GRAPHICS INPUT

- Two DVI interfaces (HDCP compliant)

POWER SUPPLY

- 1–3 kW low-ripple switch mode lamp ballast

ZOOM LENSES

- 1.25–1.45:1, 1.45–1.8:1, 1.8–2.4:1, 2.2–3.0:1, 3.0–4.3:1, 4.3–6.0:1, 5.5–8.5:1
- Available in High Brightness or High Contrast versions

LENSES (OPTIONAL)

- 1.26x Anamorphic Lens*
- Motorized mount

REFLECTOR

- F/1.5 High-Performance Compound Glass Reflector with integrated cold mirror

SAFETY INTERLOCKS

- Lamp Access Door, rear intake vent, extraction port, cable-connected lamp ballast

DOUSER

- Electronic douser – quick and quiet operation

3-AXIS (X, Y + Z) AUTOMATIC LAMP ALIGNMENT

- Christie LampLOC™
- Christie LiteLOC™
- Christie HalfLITE™

AMBIENT TEMPERATURE

- 10–35°C (50–95°F)

DIMENSIONS

- Projection head & ballast (approx., L x W x H)
42" x 25" x 16"

WEIGHT

- As installed: 260 lb max
- As shipped with packaging: 300 lb max

*Use of anamorphic lens requires motorized anamorphic lens mount added to front of the head

BRIGHTNESS (MEASURED AT SCREEN CENTER)

Lamp	Nominal	Screen Size
2.0 kW lamp (CDXL-20)	9,000 lumens	<30 ft
3.0 kW lamp (CDXL-30)	14,000 lumens	30–35 ft
3.0 kW lamp (CDXL-30SD)	17,000 lumens	35–45 ft



For the most current specification information, please visit www.christiedigital.com

Copyright 2007 Christie Digital Systems, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Canadian manufacturing facility is ISO 9001:2000 certified. DLP Cinema® is a trademark of Texas Instruments Incorporated.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada. 2151

Mar 07-NA

ISO 9001:2000



Certificate # 601



WWW.CHRISTIEDIGITAL.COM