

NEC NC1201L

Order Code: 60003926

NEC Laser Projector



The NC1201L, the second generation of an compact Digital Cinema projector using Laser Light Source, is the ideal Digital Cinema solution for smaller screens or small projection booths at the highest quality and affordable price. The 2K DCI-compliant cinema quality means an outstanding image that is bright enough to display on screens up to 12m* in DCI colour (*assuming 1.8 gain screen).

BENEFITS

Highly flexible - as no exhaust system is required, making the NC1201L suitable for floor and ceiling installation and versatile content playback.

Enjoy next to zero maintenance experience - no lamp and no filter replacement cost, no maintenance labour, no lamp stock due to the innovative Laser Light engine.

Compact and Lightweight - easy to install in small projection booths, easy to transport for mobile cinema and perfect for boothless cinema.

Enjoy Lower TCO - highest reliability, maintenance free operation, low power consumption and up to 20000 hours life time of the Laser light source results in much lower total cost of ownership.

Steady and reliable operation without any risk of black screen - much more brightness stability during the life time of the light source.

A host of integrated features - including built-in 2TB screen server, 2 x 3G SDI Interfaces, HDMI interface for alternative content, advanced network and built-in GPIO functions.

Sealed optical engine - minimising dust and smoke ingress, consistent performance is assured and maintenance reduced.



2K



OPTICAL	Projection Method	3-chip DMD reflection method
	Screen Size [m]	up to 12 in DCI colour (1.8 Gain screen)
	Contrast Ratio	1650:1
	Lamp	Laser Light Source, Expected Life: 20000 h
	Lens	Zoom / Focus / Shift: Motorized Other: Range of shift is dependent on lens Primary Lenses: NP-9LS12ZM1: 1.2-1.72:1; NP-9LS13ZM1: 1.33-2.1:1; NP-9LS16ZM1: 1.62-2.7:1; NP-9LS20ZM1: 2.09-3.9:1; NP-9LS40ZM1: 4.07-6.34:1
	DMD Specifications	2048 x 1080 Chip: 0.69" DLP
	Cooling Method	Circulating air cooling system
CONNECTIVITY IMS NP90MS02	External Controls	2 x RJ45 (4 GPI and 6 GPO); 2 x RJ45 Gigabit Ethernet
	Input Terminals	1 x USB Type 2.0; 2 x 3GSDI bidirectional (input and output); 2 x USB Type 3.0; eSATA; HDMI
	Output Terminals	2 x RJ45 (16-channel AES3-EBU Digital Audio)
	Additional Features	HFR 3D Support (48 Hz/eye, 60 Hz/eye); Integrated SMS; Integrated Storage: 2 TB (DCP, RAID5); NAS support
CONNECTIVITY PROJECTOR	External Controls	1 x GPIO (3D) (D-sub 15 pin female); 1 x GPIO (D-sub 37 pin female); 1 x RJ45 100Base-T
ELECTRICAL	Power Supply	Built-in power supply Projector Power Supply Unit: 200 to 240V AC, 50/60Hz, single phase
	Power Consumption [W]	1304 max.
ENVIRONMENTAL CONDITIONS	Operating Temperature [°C]	10 to 35
	Operating Humidity [%]	20 to 80 - non-condensing
	Storage Temperature [°C]	-10 to 50
	Storage Humidity [%]	20 to 80 - non-condensing
MECHANICAL	External Dimensions (W x H x D) [mm]	680 x 333 x 860
	Weight [kg]	66 (without lense)
	Fan Noise [dB (A)]	< 47
	Regulations Europe	CE; DCI 1.2; EN55022 1998, Class A; EN55024 1998; EN60950-1; EN61000-3-2; EN61000-3-3; IEC60825-1 Ed. 3: Class 1; TÜV-GS
	Regulations Russia	EAC; EN55022 1998, Class A; EN55024 1998; EN61000-3-2; EN61000-3-3; IEC60950-1
ADDITIONAL FEATURES	Special Characteristics	Built-in IMS; Dust sealed optical engine; Full HFR 3D support; Laser Light System; Latest digital technology; Metal filter
WARRANTY	Warranty	2 years, parts warranty
	Light Source	2 years or 7500h (whatever comes first)
GREEN FEATURES	Ecological Materials	Eliminate waste and landfill implications associated with 35mm media; Laser technology reduces power usage and reduces replacement materials required

50% of initial brightness at the end of specified laser life time.

This product has been equipped with a laser module and is classified according to Class 1 of Safety of Laser Products IEC 60825-1.

DO NOT LOOK DIRECTLY INTO THE BEAM.